

09/707,044

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS

1. (Currently Amended) A method of deconstructing video comprising:
separating a video image sequence into two or more components;
selecting a plurality of dimensions, where each dimension represents a characteristic of the video image sequence; and
encoding each component of the video image sequence in accordance with the selected dimensions to form ~~one or more~~ a plurality of bitstreams.
2. (Previously Presented) The method of claim 1 wherein said encoding step comprises:
forming a base bitstream representing a first video image sequence having a first set of characteristics; and
forming at least one additional bitstream, where each additional bitstream represents a different dimension and wherein when said base bitstream and said at least one additional bitstream are combined to form a combined bitstream, the combined bitstream represents a reconstructed video image sequence having different characteristics than said first video image sequence.
3. (Previously Presented) The method of claim 1 wherein said plurality of dimensions comprise at least one of specific image regions, frame rate, resolution, and color depth.
4. (Original) The method of claim 1 wherein the dimensions are arranged in a partial order, where each point in the partial order represents a valid combination of dimensions for encoding the video image sequence.

BEST AVAILABLE COPY

09/707,044

5. (Previously Presented) The method of claim 1 wherein each of said two or more components is encoded as at least one additional bitstream.
6. (Currently Amended) The method of claim 1 wherein all of said two or more ~~constituent~~ components are orthogonal relative to each other.
7. (Original) The method of claim 1 wherein said method is performed at the edge of a network.
8. (Original) The method of claim 1 wherein said method is performed at an intermediate node within a network.
9. (Original) The method of claim 8 wherein an intermediate node performs one or more functions selected from reconstruction, deconstruction, or a combination of deconstruction and reconstruction.
10. (Cancelled)
11. (Previously Presented) The method of claim 1 wherein, after encoding, each of said two or more components is represented by a base bitstream and at least one additional bitstream.
12. (Cancelled)
13. (Cancelled)
14. (Previously Presented) The method of claim 11 wherein said base bitstream represents a first video image sequence having minimal quality.

09/707,044

15. (Previously Presented) The method of claim 14 wherein said at least one additional bitstream, when combined with said base bitstream, represents a second video image sequence having a quality that is higher than said base bitstream.

16. (Withdrawn) A method of distributing deconstructed video through a network comprising a plurality of nodes, the deconstructed video comprising a base bitstream and a plurality of additional bitstreams that, when taken together, represent a video sequence, the method comprising:

selecting within a node said base bitstream and at least one of said additional bitstreams, wherein said selection is performed in response to a capability of a user device that is coupled to said node;

combining said base bitstream and said at least one additional bitstream to form a combined bitstream; and

propagating said combined bitstream to the user device.

17. (Withdrawn) The method of claim 16 wherein said selecting step is performed in an intermediate node within the network and said combining step is performed in an edge node.

18. (Withdrawn) The method of claim 16 wherein said selecting step is performed at the edge of a network.

19. (Withdrawn) The method of claim 16 wherein the manner of distribution of said deconstructed video through the network is selected from the following group: broadcast, pointcast, multicast.

20. (Withdrawn) The method of claim 16 wherein said at least one additional bitstream represents a dimension of said video sequence.

21. (Withdrawn) The method of claim 16 wherein said base bitstream represents a

09/707,044

video sequence having minimal quality.

22. (Withdrawn) The method of claim 21 wherein said at least one additional bitstream, when combined with said base bitstream, represents a video sequence having a quality that is higher than said base bitstream.

23. (Withdrawn) The method of claim 16, wherein the network comprises at least one transition node, where each transition node performs a method comprising:

selecting said base bitstream and at least one of said additional bitstreams for further propagation through a network that is coupled to said at least one transition node.

24. (Withdrawn) The method of claim 23 wherein said further propagation is through a second network comprising nodes that perform a method comprising:

selecting said base bitstream and at least one of said additional bitstreams, wherein said selection is performed in response to a capability of a user device that is coupled to said node in said second network;

combining said base bitstream and said at least one additional bitstream to form a combined bitstream; and

propagating said combined bitstream to the user device.

25. (Currently Amended) Apparatus for producing deconstructed video comprising:

a video component extractor for extracting at least one second image sequence from a first image sequence, where said at least one second image sequence represents a component of said first video image sequence;

an encoding dimension selector for selecting a ~~number~~ plurality of dimensions to use to encode said at least one second image sequence; and

a dimension-based encoder, coupled to said encoding dimension selector, for encoding the at least one second video image sequence into a plurality of bitstreams.

09/707,044

26. (Original) The apparatus of claim 25 wherein the dimensions are orthogonal.

27. (Original) The apparatus of claim 25 wherein the components comprise foreground, background, and moving objects.

28. (Original) The apparatus of claim 25 wherein the dimensions comprise resolution, frame rate, and color.

29. (Withdrawn) A system for generating and distributing deconstructed video comprising:

a deconstructed video source for producing a plurality of bitstreams that represent a video sequence;

a communications network, coupled to said deconstructed video source, for propagating said plurality of bitstreams; and

a plurality of network interface devices (NIDs), coupled to said network, for extracting a subset of the plurality of bitstreams and propagating said subset of bitstreams to a user device.

30. (Withdrawn) The system of claim 29 further comprising transition nodes, coupled to said network, for extracting a subset of said plurality of bitstreams from said network and coupling the subset of bitstreams to a second network.

31. (Withdrawn) The system of claim 30 further comprising NIDs coupled to said second network for extracting a further subset of the subset of bitstreams and coupling the further subset of bitstreams to a user device.

32. (Currently Amended) A computer readable medium containing software that, when executed by one or more general purpose computers operating as network nodes, causes the computer or computers to perform a method comprising:

separating a video image sequence into two or more components;

09/707,044

selecting a plurality of dimensions, where each dimension represents a characteristic of the video image sequence; and

encoding each component of the video image sequence in accordance with the selected dimensions to form ~~one or more~~ a plurality of bitstreams.

33. (Previously Presented) The method of claim 32 wherein said encoding step comprises:

forming a base bitstream representing a first video image sequence having a first set of characteristics; and

forming at least one additional bitstream, where each additional bitstream represents a different dimension and wherein when said base bitstream and said at least one additional bitstream are combined to form a combined bitstream, the combined bitstream represents a reconstructed video image sequence having different characteristics than said first video image sequence.

34. (Previously Presented) The method of claim 32 wherein said plurality of dimensions comprise at least one of specific image regions, frame rate, resolution, and color depth.

35. (Original) The method of claim 32 wherein the dimensions are arranged in a partial order, where each point in the partial order represents a valid combination of dimensions for encoding the video image sequence.

36. (Previously Presented) The method of claim 32 wherein each of said components is encoded as at least one additional bitstream.

37. (Currently Amended) The method of claim 32 wherein all of said two or more ~~constituent~~ components are orthogonal relative to each other.

38. (Original) The method of claim 32 wherein said method is performed at the edge

09/707,044

of a network.

39. (Cancelled).

40. (Previously Presented) The method of claim 32 wherein, after encoding, each of said two or more constituent components is represented by a base bitstream and at least one additional bitstream.

41. (Cancelled).

42. (Cancelled).

43. (Currently Amended) The method of claim [[.]] 40, wherein said at least one additional bitstream represents a dimension of said video image sequence.

44. (Previously Presented) The method of claim 33 wherein said base bitstream represents a first video image sequence having minimal quality.

45. (Previously Presented) The method of claim 44 wherein said at least one additional bitstream, when combined with said base bitstream, represents a second video image sequence having a quality that is higher than said base bitstream.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.